

## Technical Specifications

GSMV01	<p>1. Function: Calling/Intercom/Swipe card to unlock/Unlock door under talking by cellphone/unlock door through message by cellphone/input resident data from cellphone message</p> <p>2. Power output: DC15V</p> <p>3. Working power consumption: 0.9W(with swipe card function)/0.45W(without swipe card function)</p> <p>4. Standby power consumption: 0.45W(with swipe card function)/0.15W(without swipe card function)</p> <p>5. Material: Aluminum alloy panel, Water proof (IP55), touch keypad</p> <p>6. Working frequency: Support 850/900/1800/1900 MHz, didn't support CDMA</p> <p>7. Ambient Temperature: -20℃ ~50℃</p> <p>8. Installation: Flush mount</p> <p>9. Production Dimension (L×W×H): 155× 85× 45 mm</p>	<p>1. No need any special installation and wiring, only connect the door and power supply;</p> <p>2. No matter where you are, support speak with visitor in real time by phone and can open the door for the visitors under phone talking by simply operating;</p> <p>3. Various remote control with SMS functions.</p> <p><b>Features:</b></p> <ul style="list-style-type: none"> <li>* Aluminum alloy panel</li> <li>* Remote control from anywhere</li> <li>* Easy programming</li> <li>* Easy to install</li> <li>* Three phone numbers</li> </ul>