




**0.6M-20W LTLBSL\*N6P20**

Item Code:	LTLBSL*N6P20		Description:	IP65 Tri-Proof LED Light		<b>Product Picture</b> 
Dimension	mm	675x135x93	Viewing Angle	Degree	120	
Led Type	Taiwan chip	SMD 2835	Color Index	Ra	>80	
Led Qty	pcs	120	Power Factor	PF	>0.95	
Housing Material	PC housing+PC cover+AL board		LED forwarder Current	mA	45-50	
Luminous (LM)	1600~1800 LM		Luminous Flux (5000-5500k)	1M	470-480	
				2M	165-170	
				3M	85-90	
Luminous Efficiency	LM/W	85-95	Environment Temperature	°C	-20~+40	
Input Voltage	V	AC90~265	Waterproof	Level	IP65	
Work Voltage	V	DC36~42	Lifespan	Hr	30000	
Power Consumption	W	20W	warranty	year	3	
Color Temperature	TC	WW:3000-3500K, 4000-4500K, PW:4500-5000, 5000-5500, 5500-6000K, CW:>6000K				
Packing	Carton Size: 720*490*270mm, 6pcs/ctn, N.W.: 1.6 kgs/pc, G.W.: 14.5 kgs/ctn					


**0.6M-30W LTLBSL\*N6P30**

Item Code:	LTLBSL*N6P30		Description:	IP65 Tri-Proof LED Light		<b>Product Picture</b> 
Dimension	mm	675x135x93	Viewing Angle	Degree	120	
Led Type	Taiwan chip	SMD 2835	Color Index	Ra	>80	
Led Qty	pcs	180	Power Factor	PF	>0.95	
Housing Material	PC housing+PC cover+AL board		LED forwarder Current	mA	45-50	
Luminous (LM)	2400~2600 LM		Luminous Flux (5000-5500k)	1M	690-700	
				2M	240-245	
				3M	125-130	
Luminous Efficiency	LM/W	85-95	Environment Temperature	°C	-20~+40	
Input Voltage	V	AC90~265	Waterproof	Level	IP65	
Work Voltage	V	DC36~42	Lifespan	Hr	30000	
Power Consumption	W	30W	warranty	year	3	
Color Temperature	TC	WW:3000-3500K, 4000-4500K, PW:4500-5000, 5000-5500, 5500-6000K, CW:>6000K				
Packing	Carton Size: 720*490*270mm, 6pcs/ctn, N.W.: 9.6 kgs/ctn, G.W.: 14.5 kgs/ctn					


## 1.2M-40W LTLBSL\*N6P40

Item Code:	LTLBSL*N6P40		Description:	IP65 Tri-Proof LED Light		<b>Product Picture</b> 
Dimension	mm	1280x135x93	Viewing Angle	Degree	120	
Led Type	Taiwan chip	SMD 2835	Color Index	Ra	>80	
Led Qty	pcs	240	Power Factor	PF	>0.95	
Housing Material	PC housing+PC cover+AL board		LED forwarder Current	mA	45-50	
Luminous (LM)	3400~3600 LM		Luminous Flux (5000-5500k)	1M	940-950	
				2M	320-325	
				3M	165-170	
Luminous Efficiency	LM/W	85-95	Environment Temperature	℃	-20~+40	
Input Voltage	V	AC90~265	Waterproof	Level	IP65	
Work Voltage	V	DC36~42	Lifespan	Hr	30000	
Power Consumption	W	40W	warranty	year	3	
Color Temperature	TC	WW:3000-3500K, 4000-4500K, PW:4500-5000, 5000-5500, 5500-6000K, CW:>6000K				
Packing	Carton Size: 1320*490*270mm, 6pcs/ctn, N.W.: 16.8 kgs/ctn, G.W.: 22 kgs/ctn					

## 1.5M-50W LTLBSL\*N6P50

Item Code:	SL-P65F5-50-X		Description:	IP65 Tri-Proof LED Light		<b>Product Picture</b> 
Dimension	mm	1575X135X93	Viewing Angle	Degree	120	
Led Type	Taiwan chip	SMD 2835	Color Index	Ra	>80	
Led Qty	pcs	300	Power Factor	PF	>0.95	
Housing Material	PC housing+PC cover+AL board		LED forwarder Current	mA	45-50	
Luminous (LM)	4200~4400 LM		Luminous Flux (5000-5500k)	1M	1100-1150	
				2M	380-390	
				3M	205-210	
Luminous Efficiency	LM/W	85-95	Environment Temperature	℃	-20~+40	
Input Voltage	V	AC90~265	Waterproof	Level	IP65	
Work Voltage	V	DC36~42	Lifespan	Hr	30000	
Power Consumption	W	50W	warranty	year	3	
Color Temperature	TC	WW:3000-3500K, 4000-4500K, PW:4500-5000, 5000-5500, 5500-6000K, CW:>6000K				
Packing	Carton Size: 1620*490*270mm, 6pcs/carton, N.W.: 21 kgs/ctn, G.W.: 27 kgs/ctn					

## 1.5M-60W LTLBSL\*N6P60

Item Code:	LTLBSL*N6P60		Description:	IP65 Tri-Proof LED Light		Product Picture
Dimension	mm	1575X135X93	Viewing Angle	Degree	120	
Led Type	Taiwan chip	SMD 2835	Color Index	Ra	>80	
Led Qty	pcs	336	Power Factor	PF	>0.95	
Housing Material	PC housing+PC cover+AL board		LED forwarder Current	mA	45-50	
Luminous (LM)	5000~5200 LM		Luminous Flux (5000-5500k)	1M	1310-1350	
				2M	446-456	
				3M	245-255	
Luminous Efficiency	LM/W	85-95	Environment Temperature	°C	-20~+40	
Input Voltage	V	AC90~265	Waterproof	Level	IP65	
Work Voltage	V	DC36~42	Lifespan	Hr	30000	
Power Consumption	W	60W	warranty	year	3	
Color Temperature	TC	WW:3000-3500K, 4000-4500K, PW:4500-5000, 5000-5500, 5500-6000K, CW:>6000K				
Packing	Carton Size: 1620*490*270mm, 6pcs/carton, N.W.: 21 kgs/ctn, G.W.: 27 kgs/ctn					